

SB460

Fluorescent

460GSM PVC BANNER




Banner

PRODUCT DATASHEET

SB460ORG2070

Description	460gsm vibrant fluorescent orange PVC banner used for a variety of internal and some limited outdoor applications where bright vivid signage is required.
IMPORTANT NOTE	It is very IMPORTANT to note that SB460 Orange Glow PVC banner has very limited external light fastness properties. We would expect fading to occur within 3 months of external exposure, however this can vary dramatically depending on the directional aspect. Please note it would not be uncommon to see some degree of colour fading within weeks if subject to north facing or high UV conditions. Consideration of the project application and the end use criteria must be evaluated when considering using SB460 Orange Glow PVC Banner.
Total Weight / DIN60001	460gsm
Thickness	0.39mm
Tensile Strength (N/5cm) DIN53354	L. 600 W. 750
Tearing Strength (N/5cm) DIN53363	L. 150 W. 180
Peeling Strength (N/5cm) DIN53357	60
Temperature Resistance deg C DIN53372	-30 – +70
Roll Size	2070mm x 50m
Base Fabric Dtex	200 x 500
Density	18 x 12
<small>Data represents typical values and is not intended for use as a specification. No liability will be accepted for errors or omissions and in no circumstances are HVG or the manufacturer liable for any loss or injury arising directly, indirectly or as a consequence of the publication of this data sheet. All HVG products are supplied subject to our Terms & Conditions of sale. HVG retains the right to change specifications of products without prior notice.</small>	



INTERNAL AND
EXTERNAL



ECO-SOLVENT
PRINT



SCREEN
PRINT



LATEX
PRINT



UV
PRINT