



PRODUCT DATASHEET

Description	High-quality, gloss face, black back 270gsm Frontlit banner designed to produce great print results on high speed digital printing equipment. Light weight with super strength, a sharp white point and a surface that will enhance print quality. Ideal for use on billboards and similar grand format applications.
Features	<ul style="list-style-type: none"> • Light weight for easier installation • High Gloss face for excellent print quality • Smooth face for excellent print quality • Black back for optimum blockout opacity • HS formulation for High Speed printing • FR for Fire Retardance
Total weight	270gsm
Base Fabric	Polyester
Yarn dtex	550 x 550 dtex / 500 x 500 denier / thread 9 x 9
Tensile Strength	760 x 580 N/5cm. Test Method DIN EN ISO 1421
Tear Strength	135 x 99 N. Test Method DIN 53363
Adhesion	No delamination
Flame Resistance (FR)	NFPA 701, B1, M2. Test method DIN4102
Width	Up to 5000mm
Ink Technology	Suitable for use with; Digital – Solvent, Eco Solvent, UV, Latex Screen Printing – Solvent, UV
Shelf-life	12 – 18 months
Note	All above information shall only be used as a guide. Buyers shall independently test and determine products suitability in terms of processing procedures and end use application. The information provided is based on past test results and should not be used for the purpose of warranty.

Data represents typical values and is not intended for use as a specification. No liability will be accepted for errors or omissions and in no circumstances are HVG or the manufacturer liable for any loss or injury arising directly, indirectly or as a consequence of the publication of this data sheet. All HVG products are supplied subject to our Terms & Conditions of sale. HVG retains the right to change specifications of products without prior notice.

