

REBEL Gloss Overlamine

Gloss PVC-free Self Adhesive Lamination Film



PRODUCT DATASHEET

Description:	HVG Graphics Media's range of REBEL PVC-free films are a great alternative to, and can be used in place of traditional PVC self-adhesive vinyls. REBEL films can be used both internally and externally for all types of printed promotional graphics, retail applications and short term brand activations. These films are a versatile and economical choice for point of sale applications.
Film structure:	60 micron, polypropylene film with white glassine paper liner (liner weight 63g/m ²)
Adhesive type:	Permanent transparent polyacrylic (adhesive weight 30g/m ²)
Adhesion:	On steel: (after 24hr) - 11N/25mm, AFERA 5001
Dimensional stability:	MD: <0%, FTM 14 CD: <0%, FTM 14
Flammability:	Non self-extinguishing, DIN 75200
Print compatibility:	Recommended as a compatible overlamine for REBEL Print PVC-free film printed with all common inkjet printing platforms.
Life expectancy:	Durability is up to 1 year unprinted, pending installation location, aspect, & environmental conditions. Longevity is provided as a guideline only, and can be influenced by many variables including, but not limited to, processing techniques, surface preparation, vertical or horizontal exposure, aspect, exposure to UV & environment.
Storage & best before:	Should be kept in clean dry conditions, stored and processed between 15-25 degrees Celsius at 50% RH. Best used within 24 months from date of manufacture. Always keep product in original packaging away from direct sunlight. Condition rolls to print room at least 24 hours prior to printing.
NB: The estimated durability is based on accelerated ageing tests and refers to a vertical exposure under middle European climates. The durability of the product depends on the substrate's preparation, the atmospheric conditions and the environmental influence.	
<small>Data represents typical values and is not intended for use as a specification. No liability will be accepted for errors or omissions and in no circumstances are HVG or the manufacturer liable for any loss or injury arising directly, indirectly or as a consequence of the publication of this data sheet. All HVG products are supplied subject to our Terms & Conditions of sale. HVG retains the right to change specifications of products without prior notice.</small>	




☎ 1300 851 033
hvggraphics.com.au

fb.com/hvggraphicsmedia
 @hvggraphicsmedia

REBEL Matte Overlamine

Matte PVC-free Self Adhesive Lamination Film



PRODUCT DATASHEET

Description:	HVG Graphics Media's range of REBEL PVC-free films are a great alternative to, and can be used in place of traditional PVC self-adhesive vinyls. REBEL films can be used both internally and externally for all types of printed promotional graphics, retail applications and short term brand activations. These films are a versatile and economical choice for point of sale applications.
Film structure:	60 micron, polypropylene film with white glassine paper liner (liner weight 63g/m ²)
Adhesive type:	Permanent transparent polyacrylic (adhesive weight 30g/m ²)
Adhesion:	On steel: (after 24hr) - 11N/25mm, AFERA 5001
Dimensional stability:	MD: <0%, FTM 14 CD: <0%, FTM 14
Flammability:	Non self-extinguishing, DIN 75200
Print compatibility:	Recommended as a compatible overlaminate for REBEL Print PVC-free film printed with all common inkjet printing platforms.
Life expectancy:	Durability is up to 1 year unprinted, pending installation location, aspect, & environmental conditions. Longevity is provided as a guideline only, and can be influenced by many variables including, but not limited to, processing techniques, surface preparation, vertical or horizontal exposure, aspect, exposure to UV & environment.
Storage & best before:	Should be kept in clean dry conditions, stored and processed between 15-25 degrees Celsius at 50% RH. Best used within 24 months from date of manufacture. Always keep product in original packaging away from direct sunlight. Condition rolls to print room at least 24 hours prior to printing.
NB: The estimated durability is based on accelerated ageing tests and refers to a vertical exposure under middle European climates. The durability of the product depends on the substrate's preparation, the atmospheric conditions and the environmental influence.	
Data represents typical values and is not intended for use as a specification. No liability will be accepted for errors or omissions and in no circumstances are HVG or the manufacturer liable for any loss or injury arising directly, indirectly or as a consequence of the publication of this data sheet. All HVG products are supplied subject to our Terms & Conditions of sale. HVG retains the right to change specifications of products without prior notice.	



☎ 1300 851 033
hvggraphics.com.au

fb.com/hvggraphicsmedia
 @hvggraphicsmedia