VIEWultraflat

Blockout Matte White Pull-Up Banner



PRODUCT DATASHEET	
Description:	VIEWultraflat is a smooth single sided 305gsm blockout PET pull-up material suited to high quality internal graphic applications. Single sided with a silver back the material stays ultra-flat and can be printed with most platforms on the front side. VIEWultraflat is very popular for pull-up or roll-up POP displays as well as ceiling hung retail advertising.
Available widths:	914mm, 1370mm, 2500mm
Material:	300D x 300D, 44 x 43 Matte Polyester ((3A yarn)100%PES)
Base Caliper:	0.295mm ± 5%
Base Weight:	305gsm + 5% (DIN53352 BS3424/Method 5A)
Thickness:	295+5% micron (DIN EN ISO 2286-3)
Tensile Strength:	Warp: 1350N/5cm (DIN53352 BS3424) Weft: 1200N/5cm
Tearing Strength:	Warp: 100N/5cm (DIN53356 BS3424) Weft: 90N/5cm
External durability:	Suitable for indoor application only
Print side and settings:	Print side is wound to the inside of the roll, enhanced multi pass print quality mode should be selected
Printer compatibility:	Solvent, Eco-solvent, UV and Latex inks
Life expectancy:	External durability up to 2 years, unprinted, pending installation location, aspect, & environmental conditions. Longevity is provided as a guideline only, and can be influenced by many variables including, but not limited to, processing techniques, surface preparation, vertical or horizontal exposure, aspect, exposure to UV & environment.
Storage & best before:	Should be kept in clean dry conditions, stored and processed between 20-24 degrees Celsius at 30% – 70% RH. Best used within 12 months from date of manufacture. Always keep product in original packaging away from direct sunlight. Condition rolls to print room at least 24 hours prior to printing.

Data represents typical values and is not intended for use as a specification. No liability will be accepted for errors or omissions and in no circumstances are HVG or the manufacturer liable for any loss or injury arising directly, indirectly or as a consequence of the publication of this data sheet. All HVG products are supplied subject to our Terms & Conditions of sale. HVG retains the right to change specifications of products without prior notice.





