

PRODUCT DATA SHEET

Decobus Opaque Satin White

DESAWHREM137050, DESAWHREM1400C6,

DESAWHREM155050

opaque white PVC characterized with good flexibility and conformability. ent adhesive gives a good initial tack and easy repositioning and allows bility at the end of the advertising campaign, within a period of 6 months lication. Specifically developed for the large format solvent and UV id screen printing, for transit decoration. <i>v</i> inyl film : White , semi-gloss, ±10% ISO-536 0% ISO 534-80 SP30 anent acrylic + 10°C 0°C / +100°C H N/inch ² M1: 8 +/- 2 N/inch
: White , semi-gloss, ±10% ISO-536 0% ISO 534-80 SP30 anent acrylic + 10°C 50°C / +100°C H N/inch ²
anent acrylic + 10°C 50°C / +100°C H N/inch²
ne coated 2 side PE coated Kraft : White ±10% ISO 536 10% ISO 534
ity between media, printers and inks is always recommended prior to use.
cable only to the material delivered by Ritrama which has not undergone g, under the following STORAGE CONDITIONS:
oduct is warranted for removability, when applied to sound painted riod of 6 months from the date of application erial must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Humidity. area must be dry and clean. • material in the original packaging when not used in order to protect it t and contamination. * wpose to direct sunlight or heat sources.

• P: 1300 851 033 • F: 1300 658 889 • graphics@hvg.net.au • www.hvggraphics.com.au