

# SAHARA FROSTY CLEAR OV360

Monomeric / Promotional Films

## PRODUCT DATASHEET

<b>Description</b>	Sahara Frosty Clear OV360 0.12mm Non UV laminating film provides embossed matte finish with special anti-slippery texture for use on most cold laminating machines for protection of printing graphics. Sahara is typically used for internal floor graphics, display posters and graphics where a textured laminate is required. The film is designed for durability, wear resistance and diffuse harsh light when used in vertical poster applications. Sahara is also classified in P4 under Wet Pendulum Slip resistance classification (AS 4586: 2013).
<b>Application</b>	Over lamination
<b>Product Codes</b>	SAHOV360153050 #039782, SAHOV360137150 #039655
<b>Gloss Level</b>	Matte (#450 non glare)
<b>Material</b>	Monomeric Calendared Polyvinyl Chloride. Cadmium free.
<b>Basis Caliper</b>	4.7Mil (0.12mm)
<b>Basis Weight</b>	160 g/m <sup>2</sup> +5% (excludes adhesive & backliner weight)
<b>Available Width</b>	1370mm; 1530mm. (Other Size: Order to build at MOQ of 0.5ton)
<b>Adhesive</b>	Yes, mid tack.
<b>Option</b>	1. 120g single PE coated kraft      2. Double sides PE coated kraft
<b>Shelf Life</b>	1 year when stored in original packing at 21°C at 50% RH.
<b>Life Expectancy</b>	Relevant to site condition, exposure, wear and tear as well as end use application. If used as internal floor graphic foot traffic will impact surface. 1 month in outdoor of exposure condition, up to 3 years in indoor condition.
<b>Laminating Operation</b>	The film side is wound to the outside of the roll.
<b>Lamination</b>	These products can be operated with most cold laminators and hot laminators with temperature heater being switched off. Overlap the image with a 0.25" safe edge of laminate. This will seal the photobase paper, preventing moisture absorption and paper splitting. Use laminates of equal gauge when encapsulating to prevent image curl. Overlaminating will decrease the rate at which the images fade.
<b>Adhesive Type</b>	Permanent, mid tack, solvent based.
<b>Back Liner</b>	80 gsm kraft with PE coated on single side. (Thicker PE coated)
<b>Quick Tack</b>	10~13 N / 25mm
<b>Peel 20 min</b>	8~10 N / 25mm
<b>Peel 24 h</b>	14~16 N / 25mm
<b>Slip Resistance</b>	Meets or exceeds AS 4586:2013; Class P4

Data represents typical values and is not intended for use as a specification. No liability will be accepted for errors or omissions and in no circumstances are HVG or the manufacturer liable for any loss or injury arising directly, indirectly or as a consequence of the publication of this data sheet. All HVG products are supplied subject to our Terms & Conditions of sale. HVG retains the right to change specifications of products without prior notice. CH0924



1300 851 033  
[hvggraphics.com.au](http://hvggraphics.com.au)

[fb.com/hvggraphicsmedia](https://fb.com/hvggraphicsmedia)  
[hvggraphicsmedia](https://www.instagram.com/hvggraphicsmedia)

E.O.E. T&Cs of Sale Apply.