

FEDRIGONI

INDOOR ADVERTISING

HVG
GRAPHICS MEDIA



F-Print Natural Fibers 115 FSC™ Ultra Rem

Print, Peel, Impress, Repeat!

F-Print Natural Fibers 115 FSC™ Ultra Rem is not just a material; it's a sustainable alternative reshaping the landscape of short-term indoor advertising. Embrace the future of large-format printing with this innovative solution that combines performance, versatility, and environmental responsibility.

PATENT PENDING *

(*) italian patent pending

F-Print Natural Fibers 115 FSC™ Ultra Rem

PRODUCT DESCRIPTION

F-Print Natural Fibers 115 FSCTM Ultra Rem redefines short-term indoor advertising by challenging the dominance of traditional PVC films. Developed with a 100% post-consumer natural recycled fibers face, printable with latex and UV inks, it offers a PVC alternative without compromising print quality.

Typical uses

- Point of sales advertising
- Short term indoor windows graphics
- Indoor advertising panels

MAIN BENEFITS

PVC-free and plasticiser-free
F-Print Natural Fibers is a more sustainable alternative to any traditional plastic films.

100% post-consumer recycled fibers
The face is made with 100% recycled fibers, promoting environmental responsibility.

Reduced environmental impact
A Life Cycle Assessment (LCA) comparison with a monomeric 100µm PVC film reveals significant reductions in energy, water consumption, and CO2 emissions:

- 50% less energy consumed
- 58% less water consumed
- 48% less CO2 emission

Ultra-removable adhesive
Ensures easy removal from substrates found in point of sales like glass, Forex, Alubond, and carton.

PHYSICO-CHEMICAL PROPERTIES

FACE THICKNESS, WITHOUT ADHESIVE	120mm	ISO 534-80
FACE THICKNESS, WITH ADHESIVE	140mm	ISO 534-80
TENSILE STRENGTH DRY (MACHINE DIRECTION)	> 80 N/cm	ISO 527
TENSILE STRENGTH WET	> 15 N/cm	
ELONGATION AT BREAK (MACHINE DIRECTION) ¹	> 3%	ISO 527
DIMENSIONAL STABILITY (1 WEEK @70 °C ON GLASS)	0,2 mm	FTM 14
INITIAL ADHESION ON GLASS (20 MINUTES)	2 N/25mm	FTM 1
ADHESION ON GLASS (24 HOURS)	2.5 N/25mm	FTM 1
FINAL ADHESION ON GLASS (1 WEEK)	2.5 N/25mm	FTM 1
MINIMUM APPLICATION TEMPERATURE	+10 °C	
SERVICE TEMPERATURE	From -40 °C to +90 °C	
KRAFT PAPER LINER	80 g/m2	ISO 536



1300 851 033
hvggraphics.com.au
 E.O.E. T&Cs of Sale Apply.

fb.com/hvggraphicsmedia
[hvggraphicsmedia](https://www.instagram.com/hvggraphicsmedia)

CH 06/2026



The mark of
responsible forestry