

PRODUCT DATA SHEET

High Tack Application Paper		APPHIGH122091
Description	High Tack Application Paper is standard weight saturated paper coated with a high tack latex rubber based adhesive designed specifically for pre-masking of medium to fine sized die cut or computer cut vinyl lettering and graphics.	
Adhesive	Rubber-based	
Colour	Transparent	
Caliper facestock	93 microns (3.7 mils)	
Caliper facestock + adhesive		
Adhesion to Steel	1-4 N/100mm (1-3 oz.)	
Tensile	25MPa (3600psi)	
Elongation	700	
Tear Resistance	50	
Shelf Life	1 year	
Advantages	<ul style="list-style-type: none"> • Excellent water resistance allows for wet applications • Static free adhesive improves the lamination process • Exceptional clarity to aid precise registration of multi colour applications • Rigid polypropylene face stock minimizes misalignment • All-purpose application clear film for wet & dry applications • Excellent for transferring graphics to banners 	
Other	<ul style="list-style-type: none"> • Adhesion PSTC-1, 1 minute on stainless steel at time of manufacture • Store at 22 degrees C / 50-55 % RH • Standard roll sizes 1220mm x 91m • Removes cleanly & easily following graphics applications • Works well with either wet or dry applications with no adhesive transfer • Can be slit to your requirements, please discuss with HVG Account Manager 	
<p>Data represents typical values and is not intended for use as a specification. No liability will be accepted for errors or omissions and in no circumstances are HVG or the manufacturer liable for any loss or injury arising directly, indirectly or as a consequence of the publication of this data sheet. All HVG products are supplied subject to our Terms & Conditions of sale. HVG retains the right to change specifications of products without prior notice.</p>		

• P: 1300 851 033 • F: 1300 658 889 • graphics@hvg.net.au • www.hvggraphics.com.au