

PRODUCT DATA SHEET

Medium Tack Application Paper		APPMED61091, APPMED122091
Description	Medium Tack Application Paper is standard weight saturated paper coated with a medium tack latex rubber based adhesive designed specifically for pre-masking of small and medium sized die cut or computer cut vinyl lettering and graphics.	
Adhesive	Rubber-based	
Colour	White/Translucent	
Caliper facestock	100-113 microns (4.0 -4.5 mils)	
Caliper facestock + adhesive	125-138 microns (5.0 - 5.5 mils)	
Adhesion to Steel	18 - 20 N/100mm (16 - 18 oz.)	
Tensile	297 N/100mm (17lb./in)	
Elongation	3-4%	
Tear Resistance	50	
Shelf Life	1 year	
Advantages	<ul style="list-style-type: none"> • Premask for small and medium size vinyl graphics • All-purpose application paper for wet & dry applications • Excellent for transferring graphics to banners • Adhesion PSTC-1, 1 minute on stainless steel at time of manufacture • Store at 22 degrees C / 50-55 % RH • Standard roll sizes 1220mm x 91m, also available 610mm x 91m (2 per carton) 	
Other	<ul style="list-style-type: none"> • Removes cleanly & easily following graphics applications • Works well with either wet or dry applications with no adhesive transfer • Can be slit to your requirements, please discuss with HVG Account Manager 	
<p>Data represents typical values and is not intended for use as a specification. No liability will be accepted for errors or omissions and in no circumstances are HVG or the manufacturer liable for any loss or injury arising directly, indirectly or as a consequence of the publication of this data sheet. All HVG products are supplied subject to our Terms & Conditions of sale. HVG retains the right to change specifications of products without prior notice.</p>		

• P: 1300 851 033 • F: 1300 658 889 • graphics@hvg.net.au • www.hvggraphics.com.au