



GRAPHICS MEDIA

PRODUCT DATA SHEET

Product Code: GCPVC1000760

Issued June 2016



GRAPHICS - PROMOTIONAL

Issue date : 18/11/2008
Date last modification : 15/10/2012

00118 RI-200/80 PVC GLOSS CLEAR AP 900 WKPE 150

Face Material

Gloss clear soft vinyl.

Table with 4 columns: Property, Value, Standard 1, Standard 2. Includes Type (Soft vinyl), Colour and Finish (Gloss clear), Weight (104 g/m² ±10%), Thickness (80 µ ±10%).

Adhesive

Acrylic permanent adhesive featuring high clarity and very high cohesion. Designed for a wide variety of substrates such as glass, ABS, PS, PVC. Unsuitable for apolar surfaces (like PE and PP).

Table with 4 columns: Property, Value, Standard 1, Standard 2. Includes Reference (AP900), Type (Acrylic permanent), Min. Appl. Temp. (+10°C), Service Temp. (-30°C/+120°C), Shear (Very High), Tack (6 N/25mm), Final Adhesion (9 N/25mm).

This adhesive complies with FDA 175.105.

Liner

Table with 4 columns: Property, Value, Standard 1, Standard 2. Includes Type (Siliconised two side PE Kraft), Colour and Finish (White), Weight (144 g/m² ±10%), Thickness (155 µ ±10%), Transparency (n.a. %).

Applications

Labels, stickers and point of sale advertising with medium outdoor durability.

Printing Methods

Printable in solvent based and UV screenprinting, offset UV, hot stamping.

Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

36 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following STORAGE CONDITIONS:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
• Storage area must be dry and clean.
• Keep the material in the original packaging when not used in order to protect it from dust and contamination.
• Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.



Ritrama S.p.A.
Via Senatore Simonetta, 24
20867 Caponago (MB) ITALY
e-mail: info@ritrama.com
www.ritrama.com

