

PRODUCT DATA SHEET

ILFM Matt Silver Top-coated Aluminium Sheets		ILFM2001000700
Description	40 micron Aluminium Foil, top coated for good printability, with permanent acrylic solvent based adhesive in matte or bright. Can be printed by letterpress UV, screen-printing UV and Gravure. Suitable for labels requiring embossable variable data. Very good temperature resistance.	
Application	Nameplates, industrial instruction labels for electrical appliances and motors, dials or control panels. Product nameplates and instruction panels, embossed nameplates.	
Face Material	Type: TC Aluminium Colour and finish: Aluminium, matt Caliper: 40 micron	
Release Backing	Type: 1 side silicon coated PE kraft Colour: White Substance: 150 g/sqm Caliper: 170 micron Transparency: 0%	
Adhesive	Reference: RI – ASP5 Type: Permanent acrylic (solvent based) Min. appl. Temp: +5°C Service temp: -15°C / +120°C Cohesion: Excellent Tack: Medium Ultimate adhesion: High	
Chemical Resistance	Detergent: No effect (24Hrs) Gasoline: No effect (1 Hr) SAE20 Motoroil: No effect (24Hrs) 10% HCl: No effect (10 min) 10% NH4OH: No effect (10 min)	
Data represents typical values and is not intended for use as a specification. No liability will be accepted for errors or omissions and in no circumstances are HVG or the manufacturer liable for any loss or injury arising directly, indirectly or as a consequence of the publication of this data sheet. All HVG products are supplied subject to our Terms & Conditions of sale. HVG retains the right to change specifications of products without prior notice.		