



## PRODUCT DATA SHEET

VIEWclear Super Clear Polyester Rolls VCLPETREM150050		
Face Material Gloss clear top coated polyester.		red polyester.
	Туре	Top coated polyester
	Colour and Finish	Gloss clear
	Weight	105 g/m² ±10% ISO-536
	Thickness	75 μ ±10% ISO 534-80
Adhesive	Acrylic removable adhesive featuring high resistance to moisture. Soft peel adhesion, suitable for seal and reseal labels on wet packed products (like baby or cosmetic wipes).	
	Reference	AR807-UV Absorber
	Туре	Acrylic removable
	Min. Appl. Temp.	+10°C
	Service Temp.	-30°C/+100°C
	Shear	High
	Tack	6 N/25mm FINAT FTM9
	Final Adhesion	4 N/25mm FINAT FTM2
This adhesive complies with FDA 175.105.		
Liner	Туре	One side siliconised polyester
	Colour and Finish	Clear
	Weight	42 g/m² ±10% PP-032 - ISO 536
	Thickness	30 μ ±10% ISO 534
	Transparency	>95 % DIN 53 147-64
Applications	For applications where a good clarity is required. Suitable for temporary advertising and promotional applications. Not recommended for fan folder tags.	
Printing Methods		
	Printing methods: Ink jet UV technology, UV letterpress, UV screenprinting, gravure, hot stamping. Testing for suitability between media, printers and inks is always recommended	
	prior to use	
Shelf Life	24 months, applicable only to the material delivered by Ritrama which has not undergone	
	further processing, under the following STORAGE CONDITIONS:	
	This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative	
	Humidity.	
	Storage area must be dry and clean.	
	Keep the material in the original packaging when not used in order to protect it from dust	
	and contamination.	
	Do not expose to direct sunlight or heat sources.	
Data represents typical values and is not intended for use as a specification. No liability will be accented for errors or emissions and in no		

Data represents typical values and is not intended for use as a specification. No liability will be accepted for errors or omissions and in no circumstances are HVG or the manufacturer liable for any loss or injury arising directly, indirectly or as a consequence of the publication of this data sheet. All HVG products are supplied subject to our Terms & Conditions of sale. HVG retains the right to change specifications of products without prior notice.

• P: 1300 851 033 • F: 1300 658 889 • graphics@hvg.net.au • www.hvggraphics.com.au