

PRODUCT DATA SHEET

VIEWLam Gloss & Matt Overlamine Films		VLAMGC, VLAMMC
Description	Non-UV pressure sensitive (cold) laminating films are for use on all laminating machines for protection of printed graphics. The matt film has a slight textured embossed surface which will defuse any direct lighting.	
Applications	Laminating Graphics Point of Sale Exhibition Graphics	
Gloss Level	Gloss & Matt	
Material	Monomeric calendared polyvinyl chloride, cadmium free	
Basis Caliper	80microns (3mil)	
Basis Weight	105 g/m ² (excludes adhesive & liner weight)	
Available Width	1371mm & 1550mm	
Adhesive Type	Permanent, Mid Tack, Solvent Based Acrylic	
Back Liner	80gsm Kraft with PE coated on single side	
Quick Tack	10-13 N / 25mm	
Peel 20 min	8-10 N / 25mm	
Peel 24 h	14-16 N / 25mm	
Life Expectancy	1 Year outdoor exposure. Up to 3 years indoor conditions.	
Lamination Guidelines	The film side is wound to the outside of the roll	
Lamination Finishing Recommendations	These products can be operated with most cold laminators and hot laminators with temperature heater being switched off. Overlap the image with 0.25" safe edge of laminate and this will seal the graphic. Use laminates of equal gauge with encapsulating to prevent image curl.	
Data represents typical values and is not intended for use as a specification. No liability will be accepted for errors or omissions and in no circumstances are HVG or the manufacturer liable for any loss or injury arising directly, indirectly or as a consequence of the publication of this data sheet. All HVG products are supplied subject to our Terms & Conditions of sale. HVG retains the right to change specifications of products without prior notice.		

● P: 1300 851 033 ● F: 1300 658 889 ● graphics@hvg.net.au ● www.hvggraphics.com.au